

Flo-Master®

ALUMINUM WALL SHUTTERS

- Corrosion resistant heavy gauge aluminum frame.
- Precision counterbalanced aluminum blades open easier, wider to permit higher fan capacity.
- Nylon bearings throughout are corrosion proof to help prevent sticking. Suitable for dusty or humid applications.
- Stainless steel hinge pins will not rust, insure easy positive blade action.
- All shutter blades are reinforced with polished galvanized steel rods, and equipped with double tie-rods.
- Automatic - Used with exhaust fans; opens automatically when fan is on, closes automatically when fan is off.
- Keeps out wind, rain and backdrafts when fan is not in operation.
(See fan selection for shutter sizes)



MOTORIZED INLET SHUTTERS

- New cam pulley operator - Provides long life to motor - corrosion resistant.
- Motor draws only 17 watts.
- WAAC models are center pivoted to open easier against house static pressures.
- Motors are available in 24v, 115v, 230v, 460v, (Specify Voltage Required).

SHUTTER MODEL	DIMENSIONS			
	OVERALL	OPENING	Sq. Ft. OPENING	WT.
WAAC1818MT	18x18	15x15	1.56	10
WAAC2626MT	26x26	23x23	3.67	14
WAAC3333MT	33x33	30x30	6.25	18
WAAC4040MT	40x40	37x37	9.50	22
WAAC6318MT	63x18	60x15	6.25	19
WAAC6340MT	63x40	60x37	15.42	35
WAAC6362MT	63x62	60x59	24.58	52